





 Sonnenschein S12/130 A data sheet



Drawing:



Terminal:



Sonnenschein Solar

Sonnenschein Solar batteries are specially designed for small to medium performance applications. The advantages of the maintenance free VRLA - batteries are enhanced by the worldwide high reputation and technical image of the dryfit technology.

Sonnenschein DRYFIT SOLAR BLOCK Sealed Gel

1000 x 50% or 2000 x 25% Depth of Discharge cycles

Type	Meets	Nom. Volt V	C100 1.80 VpC	L mm	W mm	H mm	Wt. kg.
S12/6,6 S	UL94 HB	12	6.6	151.7	65.5	98.4	2.6
S12/17 G5	UL94 HB	12	17	181	76	156.4	6.1
S12/27 G5	UL94 HB	12	27	167	176	126	9.7
S12/32 G6	UL94 HB	12	32	197	132	160	11.2
S12/41 A	UL94 HB	12	41	210	175	175	14.8
S12/60 A	UL94 HB	12	60	261	136	208	19
S12/85 A	UL94 HB	12	85	353	175	190	27.3
S12/90 A	UL94 HB	12	90	330	171	236	31.3
S12/130 A	UL94 HB	12	130	286	269	230	39.8
S12/230 A	UL94 HB	12	230	518	274	238	70

The manufacturer reserves the right to change specifications without prior notice.